


Rota Tre 2.0




Standard scope of delivery

- » Profiled vermiculite firebox lining
- » Solid cast iron door with stainless steel frame
- » Air-flow handle
- » Standard external combustion air connection

The connecting piece for external combustion air supply is not included in the scope of delivery.





Triple window



Profiled vermiculite firebox lining



Ergonomic bar handle and solid cast iron door with stainless steel frame



Technical Data

Energy efficiency class		A
Connection possibility		top
Operation with external air		rear / bottom
Nominal heat output	kW	5,5
Weight (incl. packaging) steel / glass / stone	kg	119 / 109 / 119
Room heating capacity	m³	88
Length of logs	cm	30
Exhaust gas mass flow	g/s	6,0
Exhaust gas temperature	° C	282
Required discharge pressure	mbar	0,12

For all technical data please see pages 90 to 93.

Available designs	Order number	EAN-Code
Rota Tre 2.0, cover plate steel black, corpus steel black	5794 10	4029808575011
Rota Tre 2.0, cover plate glass, corpus steel black	5794 30	4029808575028
Rota Tre 2.0, cover plate Soapstone, corpus steel black	5794 22	4029808575035
Rota Tre 2.0, cover plate Sandstone, corpus steel black	5794 42	4029808575042
Rota Tre 2.0, cover plate Limestone bianco, corpus steel black	5794 89	4029808593589
Rota Tre 2.0, cover plate Ceramic Bordeaux red, corpus steel black	5794 37	4029808575066
Rota Tre 2.0, cover plate Ceramic Silk white, corpus steel black	5794 87	4029808575073
Rota Tre 2.0, cover plate Ceramic Grappa, corpus steel black	5794 32	4029808575080
Optional accessories		
Connecting piece for external combustion air supply	9200 69	4029807779991
Rotating tray black, Ø 460 mm (top connection)	9214 72	4029808539426

